

Kitemark™ Certificate

No. KM 60983

BS EN 12608-1 : 2016 + A1:2020 / PAS 24:2022 – Enhanced security performance requirements for doors in the UK.

This Certificate covers the following door system design specification. The following materials are also certificated for use with doors in conjunction with BS 7412 and PAS 24 when foiled in accordance with BS 7722:2010: Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

Imagine Bi-Folding Door System

Fabricated and installed in accordance with the latest issue of the following Veka plc controlled manual(s):

Veka UK Group Imagine Bi-Folding System Technical Manual.

System description:

The door assemblies comprise up to maximum of 7 leaves, open in or out, glazed, , double or triple glazed with at least one pane of laminated glass meeting the requirements of BS EN 356:2000, Class P1A or higher, where applicable, and shall be glazed in accordance with the BS 6262 series,, with or without midrail and/or letterplate which meets the requirements of TS008:2015 Enhanced Security Grade 2, and a handle and cylinder or cylinder guard combination achieving a minimum 3* in accordance with TS007.mechanically fixed low threshold or fully welded construction (Aluminium track). All styles excluding 2:2:0, 4:2:2, 4:4:0, 6:6:0, 6:4:2. The door sets are fitted with hardware supplied by VEKA. Doors are classified as D. Glazing is fitted with GT Securi-Clips or GT Snap-Lok.

The fitting of any connected or smart device to this product will invalidate this Kitemark Certificate unless BSI has been provided with objective evidence from a competent authority that the sensor has been tested and certified to EN 303645. BSI will update any Kitemark certificates with the relevant products as and when they have been tested

Size Limitations and Performance Characteristics

Door Type	Length (mm) - Maximum	Height (mm) - Maximum (including sill)	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1
Maximum Sash dimensions for doors with approved outer frame and sash profiles:						
Individual leaf	998	2103	3	3A	A3	1200

First Issued: 2002-04-09

Latest Issue: 2023-09-13

Effective Date: 2023-09-13

Expiry Date: 2024-08-28

Page: 12 of 15

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

Kitemark™ Certificate

No. KM 60983

Imagine Bi-Folding Door System

Classification for Operational strength in accordance with BS 6375

Operating forces	Class 2
Vertical Load	Class 2
Resistance to Static Torsion	Class 2
Soft and Heavy body Impact	Class 2
Hard Body Impact	Class 2
Load Bearing capacity of safety devices	N/A
Closure against obstruction	Pass
Resistance to opening and closing	Class 4



First Issued: 2002-04-09

Latest Issue: 2023-09-13

Effective Date: 2023-09-13

Expiry Date: 2024-08-28

Page: 13 of 15

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.